

---

B-1000  
Instant Filtered  
Water System


Installation guide



# Installation instructions.

1. Connect the pressure limiting valve (with blue mini-tap ) to the mains water supply.
2. Connect one end of the white hose provided to the blue mini-tap and connect the other end of the white hose to the Filter Module fitting labeled "IN".
3. Mount the Filter Module in an easily accessible position, preferably close to the front of the cupboard to allow for filter changes.
4. After establishing where the dispenser can be installed (within the limits of the hose length from the dispenser to Filter Module), punch a 22mm hole for mounting the dispenser.
5. Mount the dispenser by first passing the blue hose through the hole and then fitting the locking bush and lock nut to the threaded mounting shaft (see Diagram 1). Tighten the locknut. Reconnect blue hose to the out fitting.
6. Turn on the mains tap and then turn on the blue mini-tap and check for leaks. If no leaks are detected, rotate the lever on the dispenser until a good stream of water is present.

Note: There may be air bubbles in the water at first as the water filter is dry. Allow 2-3 minutes of continuous run to ensure all air bubbles have been flushed from the system.



**Billi**<sup>™</sup>  
HOME

Billi Pty Ltd  
42 Lucknow Crescent, Thomastown  
Victoria 3074 Australia

Telephone +61 3 9469 0400  
Facsimile +61 3 9469 0499

[www.billihome.com.au](http://www.billihome.com.au)

Designed and manufactured in Australia.

As Billi Pty Ltd has a policy of continual improvement, all details are subject to change without notice. All goods are sold subject to our published terms and conditions. Billi is a registered trademark. 0911